

Digits 1 2 and 3	Nominal size of the coupler or plug with interchange description
01B	1/16 sub-mini BFI original
01Y	1/16 sub-mini aerospace BFI original
02C	1/8 mini BFI original
02Y	1/8 mini aerospace BFI original
04D	1/4 Industrial
04E	FOR COUPLER: 1/4 Universal six in one FOR PLUG: 1/4 Euro high flow
04F	1/4 ARO 210
04G	1/4 Italian
04L	1/4 Lincoln long nose
04M	1/4 mold (injection mold water cooling)
04T	1/4 Automotive Truflate
06J	FOR COUPLER: 3/8 Universal three in one FOR PLUG: 3/8 Euro high flow
06K	3/8 Industrial
06M	3/8 mold (injection mold water cooling)
12N	3/4 Industrial interchange

Digit 4	Coupler or Plug and Valve Status Description
C	Coupler single shut-off (valved)
D	Coupler double shut-off (valved)
E	Coupler straight through (non valved)
K	Plug straight through (non-valved)
M	Plug valved
N	Plug safety venting straight through (non-valved)
P	Plug safety valved
V	Plug vibration control straight through (non-valved)
W	Plug vibration control valved

Digit 5	End-connect size
A	M5 and 10/32 universal thread
B	1/8
D	1/4
E	5/16
F	3/8
G	1/2
H	5/8
J	3/4
K	1
U	1/4 x .170
W	3/8 x 1/4
X	1/2 x 1/4
Y	5/8 x 1/4
Z	5/32 or 4mm

Digit 6	Type of End Connection
A	Female NPT
B	Male NPT
C	Hose Barb
D	Push Lock Barb
J	Bulkhead Panel-Mount Barb
Z	Female BSPP "G" x Male BSPP "G"
1	Reusable hose coupling (2 part)
2	Elbow 90 degree with hose barb

Digit 7	Material of machined parts
B	Brass C360 Bright Dipped
N	Brass C360 Nickel Plated
S	<u>Plugs non valved:</u> steel 12L14 yellow zinc plated <u>Plugs valved:</u> steel 12L14 yellow zinc plated profile, brass nickel plated end connect, brass valve <u>Couplers:</u> steel 12L14 sleeve, body, and insert all yellow zinc plated, brass valve, brass collar,
H	<u>Plugs non valved:</u> steel 12L14 hardened yellow zinc plated <u>Plugs valved:</u> steel 12L14 hardened yellow zinc plated profile, brass nickel plated end connect, brass valve and collar. <u>Couplers:</u> steel 12L14 hardened sleeve body and insert all yellow zinc plated, brass nickel plated end connect, brass valve, brass collar,
A	Aluminum sleeve, body, profile and end connect clear anodized. Valve, collar and insert is brass
R	303 stainless steel



Battlefield International Inc.
1664 Kohler Road, Cayuga, Ontario, CANADA N0A 1E0
Phone: 001 (905) 772-3000 Fax: 001 (905) 772-3099
Email: info@battlefield.biz
www.battlefield.biz